

# Turbo SCRAM Turbowrap & Tri Wrap



Vineyards



Pictured: 3500L 3 Row Turbo SCRAM

## MODEL SPECIFICATIONS

<b>HEAD</b>	Two row spraying head: 28 venturi air shear adjustable nozzles with individual metering and on/off taps. Three row spraying head: 42 venturi air shear adjustable nozzles with individual metering and on/off taps. Left & right arms are independent hydraulic folding with adjustable width & centre frame. Boom frame is galvanised.	<b>TANK</b>	Polytuff impact resistant polyethylene construction, calibrated sight line, flip top easy open lid, 50mm camlock bottom fill and 40L fresh water tank.				
<b>PUMP</b>	Stainless steel, hydraulic drive centrifugal pump, 350 L/min. Stainless steel shaft and Viton/ceramic seal. Driven by tractor remotes.	<b>FRAME</b>	Galvanised steel chassis, linkage hitch fitted with hydraulic power pack.				
<b>FANS</b>	320 mm turbine fan, one per air tube, 3600 rpm. Power consumed 29 kw / 38HP.	<b>AGITATION</b>	Venturi agitator.				
<b>HYDRAULIC CONTROL</b>	Hitch mounted hydraulic power pack with; 40L oil reservoir with cartridge particulate filter, motors fitted with case drain, hydraulic distribution block incorporates anti-cavitation and pressure relief valves, 12V oil cooler.	<b>FILTRATION</b>	Lid strainer and large capacity suction filter.				
<b>NOZZLES</b>	Air shear.	<b>WHEEL EQUIPMENT</b>	Tandem simplicity suspension with 10 x 15" tyres (2000L) or 11.5 x 15.3" tyres (3500L).				
<b>CONTROLS</b>	Electric section valves with Bravo 180S automatic rate controller. Large 100mm pressure gauge.	<b>PTO DRIVESHAFT</b>	Quality Bondioli & Pavesi driveshaft with quick release pins & safety cover.				
		<b>HP REQUIRED</b>	Minimum 60 PTO HP (2 row), 80 PTO HP (3 row).				
		<b>DIMENSIONS</b>	<b>L (MM)</b>	<b>W (MM)</b>	<b>H (MM)</b>	<b>KG (DRY)</b>	
		<b>STU28HB5S2</b>	4600	less head	1800	3300	990
				folded	2600		
		<b>STU38HB5S2</b>	4975	less head	1800	3300	1100
				folded	2800		
			Length measured with linkage hitch.				

## MODEL DESCRIPTION

	CODE
2000L TURBO SCRAM TRAILED 2 ROW TURBOWRAP: Includes sprayheads, 4 x 320mm fans, hydraulic drive stainless steel pump, automatic spray rate controller, self contained hydraulic drive system, tandem suspension axle	STU28HB5S2
3500L TURBO SCRAM TRAILED 2 ROW TURBOWRAP: Includes sprayheads, 4 x 320mm fans, hydraulic drive stainless steel pump, automatic spray rate controller, self contained hydraulic drive system, tandem suspension axle	STU38HB5S2
2000L TURBO SCRAM TRAILED 3 ROW TRI-WRAP: Includes sprayheads, 6 x 320mm fans, hydraulic drive stainless steel pump, automatic spray rate controller, self contained hydraulic drive system tandem suspension axle	STU28HB5S3
3500L TURBO SCRAM TRAILED 3 ROW TRI-WRAP: Includes sprayheads, 6 x 320mm fans, hydraulic drive stainless steel pump, automatic spray rate controller, self contained hydraulic drive system, tandem suspension axle	STU38HB5S3

## FACTORY OPTIONS

	CODE
Bravo 180S spray rate controller with hydraulic controls (in lieu)	J99-180
Hydraulic row width/height adjustment	-
Hydraulic pump driven through power pack	D99-185
100L Flush Tank (to suit 3500L unit)	J99-112

When ordering hydraulic drive pumps, tractor hydraulic capacity and system must be written on order. Note: Not all options will fit all models. Extra charges may apply to fitment of some options.