

Turbo SCRAM Turbowrap & Tri Wrap



Pictured: 3500L 3 Row Turbo SCRAM

MODEL SPECIFICATIONS

HEAD	Two row spraying head: 28 venturi air shear adjustable nozzles with individual metering and on/off taps. Three row spraying head: 42 venturi air shear adjustable nozzles with individual metering and on/off taps. Left & right arms are independent hydraulic folding with adjustable width & centre frame. Boom frame is galvanised.	TANK	Polytuff impact resistant polyethylene construction, calibrated sight line, flip top easy open lid, 50mm camlock bottom fill and 40L fresh water tank.			
	PUMP	Stainless steel, hydraulic drive centrifugal pump, 350 L/min. Stainless steel shaft and Viton/ceramic seal. Driven by tractor remotes.	FRAME	Galvanised steel chassis, linkage hitch fitted with hydraulic power pack.		
AGITATION			Venturi agitator.			
FANS	320 mm turbine fan, one per air tube, 3600 rpm. Power consumed 29 kw / 38HP.	FILTRATION	Lid strainer and large capacity suction filter.			
HYDRAULIC CONTROL	Hitch mounted hydraulic power pack with; 40L oil reservoir with cartridge particulate filter, motors fitted with case drain, hydraulic distribution block incorporates anti-cavitation and pressure relief valves, 12V oil cooler.	WHEEL EQUIPMENT	Tandem simplicity suspension with 10 x 15" tyres (2000L) or 11.5 x 15.3" tyres (3500L).			
		PTO DRIVESHAFT	Quality Bondioli & Pavesi driveshaft with quick release pins & safety cover.			
NOZZLES	Air shear.	HP REQUIRED	Minimum 60 PTO HP (2 row), 80 PTO HP (3 row).			
CONTROLS	Electric section valves with Bravo 180S automatic rate controller. Large 100mm pressure gauge.	DIMENSIONS	L (MM)	W (MM)	H (MM)	KG (DRY)
		STU28HB5S2	4600	less head 1800 folded 2600	3300	990
		STU38HB5S2	4975	less head 1800 folded 2800	3300	1100
Length measured with linkage hitch.						

MODEL DESCRIPTION

MODEL DESCRIPTION	CODE
2000L TURBO SCRAM TRAILED 2 ROW TURBOWRAP: Includes sprayheads, 4 x 320mm fans, hydraulic drive stainless steel pump, automatic spray rate controller, self contained hydraulic drive system, tandem suspension axle	STU28HB5S2
3500L TURBO SCRAM TRAILED 2 ROW TURBOWRAP: Includes sprayheads, 4 x 320mm fans, hydraulic drive stainless steel pump, automatic spray rate controller, self contained hydraulic drive system, tandem suspension axle	STU38HB5S2
2000L TURBO SCRAM TRAILED 3 ROW TRI-WRAP: Includes sprayheads, 6 x 320mm fans, hydraulic drive stainless steel pump, automatic spray rate controller, self contained hydraulic drive system tandem suspension axle	STU28HB5S3
3500L TURBO SCRAM TRAILED 3 ROW TRI-WRAP: Includes sprayheads, 6 x 320mm fans, hydraulic drive stainless steel pump, automatic spray rate controller, self contained hydraulic drive system, tandem suspension axle	STU38HB5S3

FACTORY OPTIONS

FACTORY OPTIONS	CODE
Bravo 180S spray rate controller with hydraulic controls (in lieu)	J99-180
Hydraulic row width/height adjustment	-
Hydraulic pump driven through power pack	D99-185
100L Flush Tank (to suit 3500L unit)	J99-112

When ordering hydraulic drive pumps, tractor hydraulic capacity and system must be written on order. Note: Not all options will fit all models. Extra charges may apply to fitment of some options.