

# 4000L Turbo SCRAM Turbowrap & Tri Wrap



Pictured: 2000L 2 Row Turbo SCRAM

## MODEL SPECIFICATIONS

<b>HEAD</b>	Two row spraying head: 28 venturi air shear adjustable nozzles with individual metering and on/off taps. Three row spraying head: 42 venturi air shear adjustable nozzles with individual metering and on/off taps. Left & right arms are independent hydraulic folding with adjustable width & centre frame. Boom frame is galvanised.	<b>TANK</b>	Polytuff impact resistant polyethylene construction, calibrated sight line, flip top easy open lid, 50mm camlock bottom fill and hand wash tank. (G2 fitted with flush tank and chemical mixer hopper)				
<b>PUMP</b>	Stainless steel, hydraulic drive centrifugal pump, 350 L/min. Stainless steel shaft and Viton/ceramic seal. Driven by tractor remotes.	<b>FRAME</b>	Galvanised steel chassis, linkage hitch fitted with hydraulic power pack.				
<b>FANS</b>	320 mm turbine fan, one per air tube, 3600 rpm. Power consumed 29 kw / 38HP.	<b>AGITATION</b>	Venturi agitator.				
<b>HYDRAULIC CONTROL</b>	Hitch mounted hydraulic power pack with; 40L oil reservoir with cartridge particulate filter, motors fitted with case drain, hydraulic distribution block incorporates anti-cavitation and pressure relief valves, 12V oil cooler.	<b>FILTRATION</b>	Lid strainer and large capacity suction filter.				
<b>NOZZLES</b>	Air shear.	<b>WHEEL EQUIPMENT</b>	Tandem simplicity suspension axle with 11.5 x 15.3" tyres.				
<b>CONTROLS</b>	Electric section valves with Bravo 180S automatic rate controller. Large 100mm pressure gauge.	<b>PTO DRIVESHAFT</b>	Quality Bondioli & Pavesi driveshaft with quick release pins & safety cover.				
		<b>HP REQUIRED</b>	Minimum 65 PTO HP (2 row), 80 PTO HP (3 row)				
		<b>DIMENSIONS</b>	<b>L (MM)</b>	<b>W (MM)</b>	<b>H (MM)</b>	<b>KG (DRY)</b>	
		<b>SETU48HB6S2</b>	5230	less head	1950	3300	1820
				folded	2800		
		<b>STU48HB6S2</b>	5730	less head	1950	3300	2000
				folded	2800		
		Length measured with linkage hitch.					

MODEL DESCRIPTION	CODE
4000L G2E TURBO SCRAM TRAILED 2 ROW TURBOWRAP: Includes sprayheads 4 x 320mm fans, Hydraulic drive stainless steel pump, automatic spray rate controller, self contained hydraulic drive system, tandem suspension axle	SETU48HB6S2
4000L G2 TURBO SCRAM TRAILED 2 ROW TURBOWRAP: Includes sprayheads 4 x 320mm fans, Hydraulic drive stainless steel pump, automatic spray rate controller, self contained hydraulic drive system, tandem suspension axle	STU48HB6S2
4000L G2E TURBO SCRAM TRAILED 3 ROW TRI-WRAP: Includes sprayheads 6 x 320mm fans, Hydraulic drive stainless steel pump, automatic spray rate controller, self contained hydraulic drive system tandem suspension axle	SETU48HB6S3
4000L G2 TURBO SCRAM TRAILED 3 ROW TRI-WRAP: Includes sprayheads 6 x 320mm fans, Hydraulic drive stainless steel pump, automatic spray rate controller, self contained hydraulic drive system, tandem suspension axle	STU48HB6S3
FACTORY OPTIONS	CODE
Bravo 180S spray rate controller with hydraulic controls (in lieu)	J99-180
Hydraulic row width/height adjustment	-
Hydraulic pump driven through power pack	D99-185
100L Flush Tank (to suit G2E)	J99-112
When ordering hydraulic drive pumps, tractor hydraulic capacity and system must be written on order. Note: Not all options will fit all models. Extra charges may apply to fitment of some options.	