Trailed Pasture Sprayer



MODEL SPECIFICATIONS				
PUMP	Silvan self-priming oil-backed diaphragm type with nitrile diaphragms & corrosion resistant cast anodised aluminium body. BP125/20: 121L/m. capacity 2000kPa pressure.			
TANK	Polytuff impact resistant polyethylene construction with calibrated sight line & non-spill screw down lid.			
CHASSIS	Galvanised RHS steel construction with adjustable drawbar and operator platform.			
AXLE	2m track axle with 14.9 x 24" lug tyre.			
BOTTOM FILL	Bottom fill with 2" camlock coupling.			

FILTER	Lid strainer, suction line filter.				
CONTROLS	3 section Silvamatic electric controls with pressure compensating direct acting valves. In cab on/off & pressure adjustment with pressure gauge.				
FLUSH TANK	100L				
FRESH WATER	Hand wash tap fitted to flush tank.				
DIMENSIONS	L (MM)	W (MM)	H (MM)	KG (DRY)	
2A0000FA	4400	2400	2500	800	
3A0000FA	4400	2400	2500	850	

MODEL DESCRIPTION	CODE	
2500L PASTURE SPRAYER: BP125/20 pump, 3 section electric valve controls		
3000L PASTURE SPRAYER: BP125/20 pump, 3 section electric valve controls		
FACTORY OPTIONS		
BP200/20 pump, 195 L/min. capacity, 2000kPa pressure		
Hydraulic drive centrifugal pump		
5 section Silvamatic electric controls (in lieu)		
Bravo 180S automatic rate controller (in lieu)		
Bravo 180S automatic rate controller to suit hydraulic control (in lieu)	J99-180	
Mudguards (to suit 14.9 x 24" wheels)	J99-162	
Adjustable track axle (minimum 1500mm) with 11.2 x 44" Lug tyres (2500L only)	J99-84	
Simplicity tandem axle with 15" Lug tyres	D99-76	
2m track axle with 31 x 13.5" Turf tyre	J99-85	
10m HD Devil boom with self levelling	032-32D	
12m HD Devil boom with self levelling		
14m HD Devil boom with self levelling*	032-48D	
15m HD Devil boom with self levelling*	032-50D	
Hydraulic lift, galvanised single hydraulic system - 10, 12, 14 and 15 HD Devil booms	032-40DL	
Airbag suspension & hydraulic lift (to suit HD Devil boom)	032-40DLAB	
Parallelogram/airbag suspension (to suit HD Devil boom)	032-40DLAB-2	
57L Paddock Foam Marker		
Silmix Chemical Hopper		
3 Section electric over hydraulic control		
5 Section electric over hydraulic control		

Note: Not all options will fit all models. Extra charges may apply to fitment of some options.
*When fitting 14 & 15m HD devil boom 032-40DLAB or 032-40DLAB-2 must be added.