Trailed Orchard Herbicide



MODEL SPECIFICATIONS

PUMP	Silvan self-priming oil-backed diaphragm type with nitrile diaphragms and corrosion resistant, cast anodised aluminium body. BP125/20: 121L/min. capacity 2000 kPa pressure
CONTROLS	3 section electric valve on/off with electric pressure adjustment from cab mounted control box.
TANK	Polytuff impact resistant polyethylene construction, calibrated sight line.
воом	6 metre fully galvanised hydraulic fold boom with stainless steel spraylines and air induction nozzles. Front mounted boom arms with independent hydraulic fold and rear mounted centre boom.

FRAME	Galvanised RHS heavy duty steel construction, jockey wheel and adjustable tow hitch.				
AGITATION	Bypass action.				
PRESSURE GAUGE	0-25 Bar dual stage glycerine filled gauge.				
FILTRATION	Lid strainer, suction line strainer & nozzle strainers.				
WHEEL EQUIPMENT	Single axle with 31/13.5 x 15" flotation tyres.				
PTO DRIVESHAFT	Quality driveshaft with quick release pins & safety cover.				
DIMENSIONS (BOOM FOLDED)	L (MM)	W (MM)	Н (ММ)	KG (DRY)	
JB2BA-125	3500	1550	2100	440	

MODEL DESCRIPTION	CODE	
2000L TRAILED ORCHARD HERBICIDE SPRAYER: BP125/20 Pump and hydraulic fold boom		
FACTORY FITTED OPTIONS	CODE	
Bravo 180S automatic spray rate controller	J99-146	
Hydraulic drive centrifugal pump	J99-126	
When ordering hydraulic drive pumps, tractor hydraulic capacity and system must be on order. Note: Extra charges may apply to fitment of some options.		