

Trailed Supaflo 2000L



Vineyards



Orchards



Pictured: 2000L Supaflo

FOR MORE
INFORMATION
ON THE RADAK
CONVEYOR
SEE PAGE 19



MODEL SPECIFICATIONS

PUMP	Silvan oil-backed diaphragm type with nitrile diaphragms and corrosion resistant, cast anodised aluminium body with brass heads and manifold. IDS1701:161L/min. capacity, 5000kPa pressure.	FRAME	Galvanised steel with jockey wheel & adjustable drawbar.			
FAN SIZE	900mm axial flow type, 10 bladed fan with curved nylon reinforced blades, air straightening vanes and protective mesh cover. Powerhead & Radak fitted with 920mm axial flow type, 10 bladed fan, centrifugal clutch and protective mesh cover.	AGITATION	Pump bypass plus venturi agitator.			
NOZZLES	Flip-over type for dilute/concentrate spraying. Ceramic jets, stainless steel swirl-plates. 16 double sided nozzles (8 per side) twist on/off. The Powerhead has 24 double sided nozzles (12 per side) and the Radak has 32 (16 per side).	PRESSURE GAUGE	100mm, 0-60 bar glycerine filled gauge with bar increments.			
GEARBOX	2-speed with neutral position, oil-bath type.	FILTRATION	Lid strainer, suction line strainer & stainless steel nozzle filters.			
CONTROLS	40 bar electric section valves, master valve, electric pressure regulator and in cab controls.	WHEEL EQUIPMENT	Glideflex suspension axle, 2 x 15" tubeless tyres on galvanised rims (max speed rating 30 km/h).			
TANK	Polytuff impact resistant polyethylene construction, calibrated sight line, flip-top easy open lid, 40mm drain valve and built-in chemical mixer. 40L fresh water hand wash tank.	PTO DRIVESHAFT	Quality Bondioli & Pavesi driveshaft with quick release pins & safety cover.			
		HP REQUIRED	Minimum 60 PTO HP.			
		DIMENSIONS	L (MM)	W (MM)	H (MM)	KG (DRY)
		DAB23AF8G	3750	1540	1530	640
			Length measured with drawbar in shortest position.			

MODEL DESCRIPTION	CODE
SUPAFLO 2000L: IDS1701 pump, 900mm fan, electric valve controls, wide angle shaft & Glideflex axle	DAB23AF8G
FACTORY OPTIONS	CODE
Powerhead Conveyor (in lieu of standard fan cowling)	D99-184
Radak Conveyor - Manual adjustment of top and bottom wings (In lieu of standard fan cowling)	D99-135
Hydraulic kit for Radak Conveyor (top wings)	D99-155B
SCRAM Jet (to suit Radak Conveyor)	D99-180
One sided conveyor	D99-41
Leaf guard (to suit Powerhead & Radak)	D99-175
Twin nozzle (includes extra nozzles)	D99-182
Two-sided poly vineyard conveyor	D99-111
Bravo 180S automatic rate controller	D99-143
Flotation tyres - 400/60 x 15.5" with fixed axle (in lieu of standard singles)	D99-80

Note: Not all options will fit all models. Extra charges may apply to fitting of some options. Fitting of Powerhead & Radak includes upgrade to 920mm fan and uprated gearbox