

# Trailed G2E 4000L



Orchards

FOR MORE  
INFORMATION  
ON THE AVO JET  
SEE PAGE 18



Pictured: 4000L G2E  
with Powerhead

## MODEL SPECIFICATIONS

<b>PUMP</b>	Silvan oil-backed diaphragm type with nitrile diaphragms and corrosion resistant, cast aluminium body with brass heads & manifolds. IDS1701:161L/min. capacity, 5000kPa pressure.	<b>CHEMICAL INDUCTION</b>	Venturi suction probe.			
	<b>FAN SIZE</b>	920mm axial flow type, 10 bladed fan with curved nylon reinforced blades, centrifugal clutch for soft engagement/disengagement and protective mesh cover.	<b>FRAME</b>	Galvanised steel, heavy duty stand & adjustable drawbar.		
<b>AGITATION</b>			Pump bypass plus venturi agitator.			
<b>NOZZLES</b>	24 flip-over nozzle bodies for dilute/concentrate spraying with on/off. 12 Ceramic hollow cone nozzles per side and 12 ceramic jets with stainless steel swirl plates per side. (16 per side with the Radak conveyor).	<b>PRESSURE GAUGE</b>	Glycerine filled gauge located on valve bank.			
		<b>FILTRATION</b>	Suction line filter, pressure filter, nozzle cup strainers.			
<b>GEARBOX</b>	2-speed with neutral position, oil-bath type.	<b>WHEEL EQUIPMENT</b>	Glideflex axle with 13.0/65 - 18" implement tyres (speed rating 30km/h).			
<b>CONTROLS</b>	40 Bar electric section valves with master valve, electric pressure regulator and in cab controls.	<b>PTO DRIVESHAFT</b>	Quality Bondioli & Pavesi constant velocity driveshaft with quick release pins & safety cover.			
<b>MAIN TANK</b>	Polytuff impact resistant polyethylene construction with calibrated sight line. 50mm Camlock top & bottom fill.	<b>HP REQUIRED</b>	Minimum 80 PTO HP.			
		<b>DIMENSIONS</b>	<b>L (MM)</b>	<b>W (MM)</b>	<b>H (MM)</b>	<b>KG (DRY)</b>
<b>HAND WASH TANK</b>	15L polytuff tank filled through cap. Located next to bottom fill.	<b>EAB43PF2G</b>	5050	1880	2020	1220
		Length measured with drawbar in shortest position.				

## MODEL DESCRIPTION

MODEL DESCRIPTION	CODE
SUPAFLO G2E 4000L: IDS1701 pump, 920mm Powerhead fan, electric valve controls, Glideflex axle	EAB43PF2G
SUPAFLO G2E 4000L: IDS1701 pump, 920mm Radak fan, electric valve controls, Glideflex axle	EAB43RF2G

## FACTORY OPTIONS

FACTORY OPTIONS	CODE
Hydraulic kit for Radak Conveyor (top wings)	D99-155B
SCRAM Jet (to suit Radak conveyor)	D99-180
AVO Jet (to suit Radak conveyor)	D99-187
Leaf guard (to suit Powerhead & Radak)	D99-176
Twin nozzles (includes extra nozzles)	D99-182
Bravo 180S automatic rate controller	D99-143
Tandem suspension axle with 11.5/80 - 15.3 tyres	D99-78
BKT flotation tyres - 558-400/55 - 22.5 (in lieu of singles)	D99-79
IDS2001 pump, 182L/min. capacity, 5000kPa pressure	D99-148
IDS2600 pump, 249L/min. capacity, 5000kPa pressure.	D99-149

Note: Not all options will fit all models. Extra charges may apply to fitment of some options.