

Trailed G2E 4000L



Orchards

FOR MORE
INFORMATION
ON THE AVO JET
SEE PAGE 18



Pictured: 4000L G2E
with Powerhead

MODEL SPECIFICATIONS

PUMP	Silvan oil-backed diaphragm type with nitrile diaphragms and corrosion resistant, cast aluminium body with brass heads & manifolds. IDS1701:161L/min. capacity, 5000kPa pressure.	CHEMICAL INDUCTION	Venturi suction probe.			
FAN SIZE	920mm axial flow type, 10 bladed fan with curved nylon reinforced blades, centrifugal clutch for soft engagement/disengagement and protective mesh cover.	FRAME	Galvanised steel, heavy duty stand & adjustable drawbar.			
NOZZLES	24 flip-over nozzle bodies for dilute/concentrate spraying with on/off. 12 Ceramic hollow cone nozzles per side and 12 ceramic jets with stainless steel swirl plates per side. (16 per side with the Radak conveyor).	AGITATION	Pump bypass plus venturi agitator.			
GEARBOX	2-speed with neutral position, oil-bath type.	PRESSURE GAUGE	Glycerine filled gauge located on valve bank.			
CONTROLS	40 Bar electric section valves with master valve, electric pressure regulator and in cab controls.	FILTRATION	Suction line filter, pressure filter, nozzle cup strainers.			
MAIN TANK	Polytuff impact resistant polyethylene construction with calibrated sight line. 50mm Camlock top & bottom fill.	WHEEL EQUIPMENT	Glideflex axle with 13.0/65 - 18" implement tyres (speed rating 30km/h).			
HAND WASH TANK	15L polytuff tank filled through cap. Located next to bottom fill.	PTO DRIVESHAFT	Quality Bondioli & Pavesi constant velocity driveshaft with quick release pins & safety cover.			
		HP REQUIRED	Minimum 80 PTO HP.			
		DIMENSIONS	L (MM)	W (MM)	H (MM)	KG (DRY)
		EAB43PF2G	5050	1880	2020	1220
			Length measured with drawbar in shortest position.			

MODEL DESCRIPTION

MODEL DESCRIPTION	CODE
SUPAFLO G2E 4000L: IDS1701 pump, 920mm Powerhead fan, electric valve controls, Glideflex axle	EAB43PF2G
SUPAFLO G2E 4000L: IDS1701 pump, 920mm Radak fan, electric valve controls, Glideflex axle	EAB43RF2G

FACTORY OPTIONS

FACTORY OPTIONS	CODE
Hydraulic kit for Radak Conveyor (top wings)	D99-155B
SCRAM Jet (to suit Radak conveyor)	D99-180
AVO Jet (to suit Radak conveyor)	D99-187
Leaf guard (to suit Powerhead & Radak)	D99-176
Twin nozzles (includes extra nozzles)	D99-182
Bravo 180S automatic rate controller	D99-143
Tandem suspension axle with 11.5/80 - 15.3 tyres	D99-78
BKT flotation tyres - 558-400/55 - 22.5 (in lieu of singles)	D99-79
IDS2001 pump, 182L/min. capacity, 5000kPa pressure	D99-148
IDS2600 pump, 249L/min. capacity, 5000kPa pressure.	D99-149

Note: Not all options will fit all models. Extra charges may apply to fitment of some options.