

Silvan Cannon Jet Sprayer



Flowers



Greenhouse



Vegetables



MODEL SPECIFICATIONS

PUMP	Silvan oil-backed diaphragm type with nitrile diaphragms, corrosion resistant, cast anodised aluminium body. APS96: 88L/min. capacity, 5000kPa pressure APS121: 115L/min capacity, 5000kPa pressure.			
FAN SIZE	450mm diameter twin turbine fan with galvanised frame and spray head. Hydraulic angle adjustment and manual top wing adjustment.			
NOZZLES	Flip-over type with ceramic hollow cone nozzles. 9 nozzles (6 in cannon head, 3 in side of cannon) with twist on/off.			
GEARBOX	Two speed with neutral position, oil-bath type.			
CONTROLS	40 bar electric section valves, master valve, electric pressure regulator and in cab controls.			
TANK	Polytuff impact resistant polyethylene construction, calibrated sight line, non-spill lid. 40 litre fresh water tank fitted to 2000L unit.			
FRAME	500L: Galvanised steel, suit cat I & II linkage 2000L: Galvanised steel with jockey wheel & adjustable drawbar.			
AGITATION	500L: Dual bypass 2000L: Pump bypass plus venturi agitator.			
PRESSURE GAUGE	100mm, 0-60 bar glycerine filled gauge with bar increments.			
FILTRATION	Lid strainer, suction line strainer and stainless steel nozzle filters.			
2000L WHEEL EQUIPMENT	Glideflex suspension axle, 2 x 15" tubeless tyres on galvanised rims (max speed rating 30 km/h).			
PTO DRIVESHAFT	Quality driveshaft with quick release pins and safety cover.			
HP REQUIRED	Minimum 75HP.			
DIMENSIONS	L (MM)	W (MM)	H (MM)	KG (DRY)
D05JET-96	1400	1190	2500	140
D20JET-121GL	3750	1540	2500	640
Length measured with drawbar in shortest position.				

MODEL DESCRIPTION

CANNON JET 500L: APS96 pump, Cannon jet fan, electric valve controls

CANNON JET 2000L: APS121 pump, Cannon jet fan, electric valve controls, Glideflex axle

FACTORY OPTIONS

Bravo 180S automatic rate controller

Extra charges may apply to fitment of some options.

CODE

D05JET-96

D20JET-121GL

CODE

D99-143