

Trailed P55DS 2000L Turbomiser



Vineyards



Orchards



AVAILABLE WITH
TURBOMISER
HEAD OPTIONS
SEE PAGE 32



Pictured: 2000L with optional Turbo Tower

MODEL SPECIFICATIONS

PUMP	CD32 centrifugal pump, 140L/min constructed from toughened nylon. Stainless steel shaft and viton/ceramic seal.	TANK	Polytuff impact resistant polyethylene construction, calibrated sight line, large non-spill flip top lid, built-in Chemical mixer and 40L fresh water hand wash tank.			
FAN SIZE	P55DS: 550mm dia. turbine fan, 3700 rpm. Power consumed 50 kw / 70HP.	AGITATION	Pump bypass plus venturi agitator.			
NOZZLES	Air shear.	FILTRATION	Lid strainer and large capacity suction filter.			
GEARBOX	Multiplication type through multi-grip, multi-vee belt and pulley, over-run free wheeling hub & oil bath fan housing.	WHEEL EQUIPMENT	Glideflex suspension axle, 2 x 15" tubeless tyres on galvanised rims (max speed rating 30 km/h).			
CONTROLS	Two sided electric on/off control with pressure regulation operated from control box mounted in cabin. Rotary plate distribution regulators with 15 settings. Large 100mm pressure gauge.	PTO DRIVESHAFT	Quality Bondioli & Pavesi driveshaft with quick release pins & safety cover.			
FRAME	Galvanised steel chassis, adjustable drawbar with jockey wheel.	HP REQUIRED	Minimum 70 PTO HP.			
		DIMENSIONS	L (MM)	W (MM)	H (MM)	KG (DRY)
		GTM20P-P55DSGL (LESS HEAD)	3970	1540	1350	650
			Length measured with drawbar in shortest position.			

MODEL DESCRIPTION	CODE
2000L P55DS TRAILED TURBOMISER: P55DS fan, Glideflex axle, wide angle PTO shaft (spray head not included)	GTM20P-P55DSGL
2000L P55DS TRAILED TURBOMISER: P55DS fan, Glideflex axle, wide angle PTO shaft, automatic rate controller, Hypro hydraulic pump (spray head not included)	GTM20P-P55DSGHL P
FACTORY OPTIONS	CODE
Vineyard head - 4 head (4x5)	GT55D-40
Hi Lo Orchard Head (4 outlets)	GT55D-6
Turbo Tower head (6 outlets)	GT55D-7
Orchard Cannon head	GT55-13
Bravo 180S automatic rate controller	GT-24
Hydraulic drive pump	GT55-22
Tandem suspension axle	D99-76

When ordering hydraulic drive pumps, tractor hydraulic capacity and system must be written on order. Note: Not all options will fit all models. Extra charges may apply to fitment of some options. Sprayer depicted with optional sprayhead.